




I-CON EVO wallboxes are JOINON solutions designed to integrate into private and semi-public scenarios in compliance with the international standard IEC 61851-1 ed. 3. They feature an elegant and compact design, special "one-hand charge" functionality and the presence of a vandal-proof socket, IP55 degree combined with IK10-certified mechanical resistance, full connectivity to support the dedicated JOINON EVO App for a complete and easy charging control, intelligent load management and energy produced by any photovoltaic panels (also in Master/Slave mode), and different installation options: wall, recessed or floor.

INPUT		- Socket/Connector Nr. (Type)	1 (Type 2 connector with 5 mt. cable)
Terminal blocks	5 x 10 mm ²	Charging activation	Free access
Current nominal	16 A	Human Interface	Led RGB
Total power	11 Kilowatt	Connectivity	Nu
OUTPUT		- MECHANICAL FACTS	-
Tensiune nominală	400 V	Mounting and installation	Wall mounting (floor mounting with support)
Current supplied (max)	16 A	Culoare	Gri închis
Maximum current	11 Kilowatt	Material	Thermoplastic (Post-industrial origin)
Thermal-magnetic protection	Currently not present	External treatments	Nu
Tip de protecție diferențială	Currently not present	Clasă de protecție IP	IP55
Contor energie	Currently not present	Cod IK	IK10
DC Leakage check	Da	Temperatură de operare	-25 +50 °C
(Auto)restart electrical protections	Currently not present	Customizations	Yes (front)

DIMENSIONAL



TECHNICAL SYMBOLOGY

IP

IP55

IK

IK10

STANDARDS/APPROVALS



GEWISS S.p.A. Via A. Volta, 1
24069 Cenate Sotto - Bergamo - Italy
tel. +39 035 94 61 11 fax +39 035 94 69 09

www.gewiss.com
sat@gewiss.com
Last update 02/08/2023

Data, measures, designs and pictures are shown only as informative purposes, and could be changed without previous notice